



## Single Mode Standard Coupler (SMC series)

The SMC Single Mode Standard Couplers are based on BTF technology. They offer very low insertion loss, low polarization dependence and excellent environmental stability. Accurate coupling ratio from 50/50 to 1/99 are available with very tight uniformity. These components find extensive application to perform power splitting and monitoring functions in all kinds of optical communication systems.



### Specifications

Parameters	Unit	Values			
Grade		P			
Operating Wavelength	nm	1310 or 1550			
Bandwidth	nm	± 20			
Coupling Ratio	%	01/99	05/95	10/90	50/50
Max. Insertion Loss	dB	21.5/0.2	14.6/0.4	10.8/0.6	3.4
Max. PDL(Tap/Through Port)	dB	0.3/0.05	0.3/0.05	0.25/0.05	0.05
Max Excess Loss	dB	0.15			
Thermal Stability	dB/	0.002dB/ over -5 °C to +70 °C			
Directivity	1X2	55 dB			
	2X2	65 dB			
Configuration		1X2 or 2X2			
Fiber length		1 meter, others on request			
Fiber type		Corning SMF-28			
Package Dimensions		250um bare fiber and dia. 3.0 mm X 55 mm			
		900um loose tube and dia. 3.0 mm X 60 mm			
		3mm loose cable and 95.5mm X 11.8mm X6.3mm			
Operating Temperature		-5 °C to +70 °C			

\*The above specification is for coupler without connector

\*For devices with connectors, insertion loss will be 0.3dB higher, RL will be 5dB lower.

### Ordering Information

**SMC-** - - - - -

:Port	:Grade	:Fiber type
1 - 1X2	P - P grade	B - 250 um bare fiber
2 - 2X2	S - Specify	L - 900 um loose tube
		C - 3mm loose cable
: Wavelength	:Connector Type	:Fiber Length
31 - 1310	1 - FC/UPC	1 - 1m
55 - 1550	2 - ST/UPC	S - Specify
SS - Specify	3 - LC/UPC	
: Coupling Ratio	4 - FC/APC	: Fiber Option
01 - 01/99	5 - SC/APC	F - Corning SMF-28
05 - 05/95	6 - SC/UPC	S - Specify
10 - 10/90	N - None	
50 - 50/50	S - Specify	
SS - Specify		